

WEBBGLIDE DUAL SHADE SYSTEM PRODUCT SPECIFICATIONS

- Shade Fabric:** Front shade (room side) fabric shall be blackout or privacy fabric of type, quality, weight, and color (to be specified). Rear shade (window side) fabric shall be a light filtering fabric (to be specified). All fabrics must be of vinyl, polyester, or fiberglass coated or backed woven material of suitable strength and resilience to roll without wrinkling, and to be cut without unraveling or hemming. Fabric shall be flame retardant to NFPA small scale test.
- Lift Roller:** Roller tubes shall be extruded aluminum alloy 6061 or 6063, 1.75" diameter with exterior .15" x .84" slot for attaching shade fabric using .0625" x .3125" extruded PVC guide slats to provide horizontal adjustment of shade fabric while preventing removal of fabric after installation. Inner lift spring to be constructed of .058" blue spring steel Drive pins to be heat-treated 1" x .024" steel.
- Glide Control:** Fabric shall be heat-sealed around a .625" galvanized steel tube at bottom of shade to provide stiffening and allow for the insertion of shade weights as required to properly balance lifting mechanism depending on weight and size of shade. Injection-molded thermoplastic guide tips shall be attached at each end with stainless steel compression springs and aluminum rivets, and shall fit easily in side tracks to provide braking system for shade.
- Brackets:** Shall be constructed of 18 gauge galvanized steel with embossed drive pin slots, and .25" x .562" nylon bushing inserts pressed into each idler pin aperture. Each bracket shall have a .5" x 2.75" lip for attaching valance. Brackets shall be constructed to accommodate two separate roller lift tubes, and shall be 4.625" x 4.625"
- Guide Tracks:** Shall be extruded from thermoplastic resin containing UV inhibitors, .5" x .875" and shall have a 1" extended lip on the inside edge to maintain privacy and reduce sunlight transmittance. Tracks shall be attached using double-coated foam adhesive PSA tape.
- Valance:** Shall be self fabric made from the privacy or blackout fabric, attached to standard 1 x 2 douglas fir headboard, 6" in length, and hemmed. Returns if required have a heat sealed corner and can be attached to headboard with staples. Headboard shall be attached to lip on bracket plate with screws.
- Or:
- Shall be extruded rigid vinyl or ABS, 5.5" high with simple half-round trim top and bottom, with slots for fabric insert. Fabric insert to be same as blackout or privacy shade fabric. Returns if required shall have mitered corners with continuous fabric. Valance extrusion shall be mounted to lip on bracket plate with screws.

